



#### ELEVATION

#### NOTES

1. FOR PAVED AREAS (INCLUDING SIDEWALKS) SEE CLEANOUT COVER ASSEMBLY DETAIL.
2. VERTICAL CLEANOUT RISER STUB SHALL BE 4 FEET OR LESS BELOW SURFACE FOR UNIMPROVED LOTS AND PROVIDED WITH A WATER TIGHT PLUG. LOCATION IS TO BE MARKED WITH A 2"x6" BOARD EXTENDING ONE FOOT MIN. ABOVE GRADE.
3. A FLEXIBLE COUPLING WILL BE REQUIRED BETWEEN THE MAIN AND THE CLEANOUT WYE BRANCH IF THE WYE IS A DIFFERENT MATERIAL THAN THE PIPE.
4. IF A PVC WYE IS USED, IT SHALL BE SET ON ITS SIDE WITH TWO 45 DEGREE BENDS WITH A SHORT SPOOL PIECE BETWEEN THE BENDS.

STANDARD SYMBOL 

CHARLES COUNTY GOVERNMENT

DEPARTMENT OF PLANNING & GROWTH MANAGEMENT

APPROVED:

DIRECTOR OF DEVELOPMENT SERVICES DATE

WATER / SEWER ENGINEER

DATE

STANDARD DETAIL

STANDARD CLEAN-OUT  
NON-TRAFFIC AREA

REVISIONS:

S  
4.03